

**C263**

Special cable composed by:

**Technical characteristics:**

Cond Number Nominal Section	<b>5x0,75 Ohm</b>
Formation	<b>10 x 0,10</b>
External Dimension (mm)	<b>9,8</b>
External core (mm)	<b>2,8</b>
Conductor Resistance Ohm/Km ±5%	<b>210</b>
Operative Temperature (°C)	<b>-15°/+70°</b>
Capacity (pF/mt) core/shield	<b>67</b>
Max operative Voltage V	<b>AC 49V</b>
Impedance Ohm	<b>75</b>
Attenuation db/100 mt 50Mhz	<b>19,5</b>
Attenuation db/100 mt 100Mhz	<b>28,5</b>
Attenuation db/100 mt 200Mhz	<b>35,6</b>
Attenuation db/100 mt 400Mhz	<b>60,0</b>
Attenuation db/100 mt 860Mhz	<b>90,0</b>
Spool or Reel	<b>100</b>
Spool kind	<b>B8</b>
Weight Kg	<b>13,0</b>

**Description:**

Special cable composed by:

5 x RGB 75 (75 ohm)  
 100% spiral shielded - tinned copper  
 Conductors in red copper  
 Conductor insulation in compact PE  
 Sheath in PVC  
 Sheath colours: white, black, red, green, blue  
 Impedance 75Ohm  
 Velocity of propagation 66%  
 Sheath in PVC colour: grey

**Cable for special video applications****Available colours:**
 Grey